

RIPPING CHISELS

Our 3 bar finishing **Ripper Chisel** is an effective implement for loosening soil up to 15 inches deep. The rigid shank design insures consistent depth. The narrow 12" shank spacing is excellent for breaking up and incorporating of residue. These ripping chisels are the perfect tool for opening up heavy soils for aeration. The main shank bars are on 3 foot centers and shanks are staggered to obtain maximum trash clearance. A large number of cross tubing braces are placed between the shank beams for added strength. The shear bolt shanks allow for higher speeds than most tillage implements.



RIPPING CHISELS

FEATURES

- Cat. III & IV narrow, 3-point quick hitch compatible
- Frame 5" x 5" x 1/4" wall steel tube
- 3 Shank beams on 36" center
- Cross braces
- 4 Tubing braces to support top mast
- Welded shank pockets
- 1 1/4" x 30" Long rigid plow steel shanks w/shear bolt protection
- Shanks are on 12" centers
- 3/4" x 15" Reversible spike points
- Pair of single gauge wheels - 9.5L x 15
- Rear clevis hitch

OPTION:

- Dual in lieu of single gauge wheels



*Heavy 2 Position Gauge
Wheels With Turnbuckle*



*Large Reversible Points
Held By 2 bolts*



*Reversible Hitch Pins
Cat. III & IV N*

Your Gearmore Dealer:



Bianchi Ag Services, LLC
CASE II

1210 Richvale Hwy.
Richvale, CA 95974
Ph: 530.882.4575
Fax: 530.882.4576

SPECIFICATIONS:

MODEL NO.	WIDTH	DESCRIPTION	NO. OF SHANKS	WEIGHT
GRC-15	15 ft.	Ripper Complete	15	
GRC-17	17 ft.	Ripper Complete	17	
GRC-19	19 ft.	Ripper Complete	19	
GRC-21	21 ft.	Ripper Complete	21	5350#

Other widths available on request