BWImplement

Vineyard Wheel Tandem Disc

V.W.T.M.D

Medium duty frame constructed with hydraulically controlled wheel transport and depth control cylinder.

Tongue leveling rod for maximum leveling control.

Easy pull pin adjustable gangs.

Full range of widths for various vineyards.

Self aligning trunnion mounted bearings.

V.W.T.H.D.

Heavy duty frame construction with solid steel gang beams for maximum depth of soil penetration.

Hydraulically controlled heavy duty wheel transport and depth control cylinder.

Tongue leveling rod for maximum leveling control.

Hand crank gang adjustment for precise cutting angle front and rear.

Self aligning trunnion mounted bearings.

288 W. Front St. - Buttonwillow, CA. 93206 - Ph: (661)764-5254 - Fax: (661)764-5253 - www.BWImp.com

Medium Duty Vineyard Tandem Disc

Model	No. of Blades	Cut Width	Blade Size	Approx. Wt.
VWTMD24-12	12	4'2"- 5'2"	24"	2240
VWTMD24-14	14	5'8"-6'8"	24"	2360
VWTMD24-16	16	5'8"-7'0"	24"	2480
VWTMD24-18	18	7'2"-8'6"	24"	2600
VWTMD24-20	20	7'2"-8'6"	24"	2720
VWTMD24-22	22	8'8"-9'8"	24"	2870
VWTMD24-24	24	8'8"-9'8"	24"	2990

Frame: 4" x 4" structural tubing
Gang Frame: Fully adjustable front and rear
Hitch: Self leveling, spring cushioned hitch w/ hand crank
Bearing & Axles: 1 ½" square axles with greasable trunnion mounted bearings with wear shield
Blades: 24" x 4.5mm smooth blades
Spools: 9" steel spacer spools & cast iron half spools
Hydraulics: Hydraulic 3 ½ ' x 8" cylinder with depth control
Shank: 1" x 3" center shank with adjustable footpiece
Wheels & Tires: 6-bolt hub and spindle assemblies with 9.5L x 15" 8-ply tire

Heavy Duty Vineyard Tandem Disc

Model	No. of Blades	Cut Width	Blade Size	Approx. Wt.
VWT24HD-16T	16	5'8"-7'0"	24"	3760
VWT26HD-16T	16	5'8"-7'0"	26"	3784
VWT24HD-18T	18	7'2"-8'6"	24"	3950
VWT26HD-18T	18	7'2"-8'6"	26"	4058
VWT24HD-20T	20	7'2"-8'6"	24"	4125
VWT26HD-20T	20	7'2"-8'6"	26"	4400
VWT24HD-22T	22	8'8"-9'8"	24"	4320
VWT26HD-22T	22	8'8"-9'8"	26"	4452
VWT24HD-24T	24	8'8"-9'8"	24"	4515
VWT26HD-24T	24	8'8"-9'8"	26"	4659

Frame: 4" x 6" structural tubing
Gangs Beams: 2"x 7" solid steel beams with 1 ½" square axles
Hitch: Self-leveling, spring cushioned hitch with hand crank
Bearing & Axles: 1 ½" square axles with greasable trunnion mounted bearings with wear shield
Spools: 9" steel spacer spools and cast iron half spools
Hydraulics: 3 ½" x 8" hydraulic cylinder with depth control and hoses
Shank: 1" x 3" center shank with adjustable footpiece
Wheel & Tires: 8-bolt hub with 11L x 15" 8-ply tires

B.W. Implement Co. is a designer and manufacturer of quality agricultural products, providing quality parts and service to meet its customer's needs. We have been located in Buttonwillow, California since 1948. Desinged and manufactured in the west for tough west conditions.

288 W. Front St. - Buttonwillow, CA. 93206 - Ph: (661)764-5254 - Fax: (661)764-5253 - www.BWImp.com